


# 深沟球轴承




## 深沟球轴承->6000 系列




轴承 型号	孔径		外径		宽度		额定载荷 (KN)		钢球参数		极限转速		参考重量 千克
	d		D		B		动负荷	静负荷	数量	尺寸 毫米	脂	油	
	毫米	英寸	毫米	英寸	毫米	英寸	Cr	Cor			转/分	转/分	
6000	10	0.3937	26	1.0236	8	0.315	4.55	1.95	7	4.763	29000	34000	0.019
6001	12	0.4724	28	1.1024	8	0.315	5.10	2.39	8	4.763	26000	30000	0.022
6002	15	0.5906	32	1.2598	9	0.3543	5.60	2.84	9	4.763	22000	26000	0.030
6003	17	0.6693	35	1.378	10	0.3937	6.80	3.35	10	4.763	20000	24000	0.039
6004	20	0.7874	42	1.6535	12	0.4724	9.40	5.05	9	6.350	18000	21000	0.069
6005	25	0.9843	47	1.8504	12	0.4724	10.10	5.85	10	6.350	15000	18000	0.080
6006	30	1.1811	55	2.1645	13	0.5118	13.20	8.30	11	7.144	13000	15000	0.120
6007	35	1.3779	62	2.4409	14	0.5512	16.00	10.30	11	7.938	12000	14000	0.160
6008	40	1.5748	68	2.6772	15	0.5906	16.80	11.50	12	7.938	10000	12000	0.190
6009	45	1.7716	75	2.9528	16	0.6299	21.00	15.10	12	8.731	9200	11000	0.250
6010	50	1.965	80	3.1496	16	0.6299	21.80	16.60	13	8.731	8400	9800	0.260
6011	55	2.1653	90	3.5433	18	0.7087	28.30	21.20	12	11.000	7700	9000	0.390
6012	60	2.362	95	3.74	18	0.7087	29.50	23.20	13	11.000	7000	8300	0.420
6013	65	2.559	100	3.937	18	0.7087	30.50	25.20	13	11.112	6500	7700	0.440
6014	70	2.7559	110	4.3307	20	0.7874	38.00	31.00	13	12.303	6100	7100	0.600
6015	75	2.9528	115	4.5276	20	0.7874	39.50	33.50	14	12.303	5700	6700	0.640
6016	80	3.1496	125	4.9213	22	0.8661	47.50	40.00	14	13.494	5300	6200	0.850
6017	85	3.3465	130	5.1181	22	0.8661	49.50	43.00	14	14.000	5000	5900	0.890
6018	90	3.5433	140	5.5118	24	0.9449	58.00	49.50	14	15.081	4700	5600	1.150
6019	95	3.7402	145	5.7087	24	0.9449	60.50	54.00	14	15.081	4500	5300	1.200
6020	100	3.937	150	5.9055	24	0.9449	60.00	54.00	14	16.000	4200	5000	1.250

### 深沟球轴承->6200 系列




轴承 型号	孔径		外径		宽度		额定载荷 (KN)		钢球参数		极限转速		参考重量 千克
	d	D	B	动负荷	静负荷	数量	尺寸	脂	油	脂	油		
	毫米 英寸	毫米 英寸	毫米 英寸	Cr	Cor	毫米	转/分	转/分	转/分	转/分			
6200	10	0.3973	30	1.1811	9	0.3543	5.10	2.39	8	4.763	25000	30000	0.032
6201	12	0.4724	32	1.2598	10	0.3937	6.10	2.75	7	5.953	22000	26000	0.037
6202	15	0.5906	35	1.3779	11	0.4331	7.75	3.60	8	5.953	19000	23000	0.045
6203	17	0.6693	40	1.5748	12	0.4724	9.60	4.60	8	6.747	18000	21000	0.065
6204	20	0.7874	47	1.8504	14	0.5512	12.80	6.65	8	7.938	16000	18000	0.110
6205	25	0.9843	52	2.0472	15	0.5906	14.00	7.85	9	7.938	13000	15000	0.130
6206	30	1.1811	62	2.4409	16	0.6299	19.50	11.30	9	9.525	11000	13000	0.200
6207	35	1.3779	72	2.8346	17	0.6693	25.70	15.30	9	11.112	9800	11000	0.290
6208	40	1.5748	80	3.1496	18	0.7087	29.10	17.80	9	12.000	8700	10000	0.370
6209	45	1.7716	85	3.3465	19	0.748	32.50	20.40	10	12.000	7800	9200	0.410
6210	50	1.965	90	3.5433	20	0.7841	35.00	23.20	10	12.700	7100	8300	0.460
6211	55	2.1653	100	3.937	21	0.8268	43.50	29.20	10	14.288	6400	7600	0.610
6212	60	2.362	110	4.3307	22	0.8661	52.50	36.00	10	15.081	6000	7000	0.780
6213	65	2.559	120	4.7244	23	0.9055	57.50	40.00	10	16.669	5500	6500	0.990
6214	70	2.7559	125	4.9213	24	0.9449	62.00	44.00	11	16.462	5100	6000	1.050
6215	75	2.9528	130	5.1181	25	0.9843	66.00	49.50	11	17.462	4800	5600	1.200
6216	80	3.1496	140	5.7087	26	1.0236	72.50	53.00	11	18.256	4500	5300	1.400
6217	85	3.3465	150	5.9055	28	1.1024	83.50	64.00	11	19.844	4200	5000	1.800
6218	90	3.5433	160	6.2992	30	1.1811	96.00	71.50	10	22.225	4000	4700	2.150
6219	95	3.7402	170	6.6929	32	1.2598	109.00	82.00	10	24.000	3700	4400	2.600
6220	100	3.937	180	7.0866	34	1.3386	122.00	93.00	10	25.400	3500	4200	3.150

### 深沟球轴承->6300系列




轴承 型号	孔径		外径		宽度		额定载荷 (KN)		钢球参数		极限转速		参考重量 千克
	d	D	B	动负荷	静负荷	数量	尺寸	脂	油	脂	油		
	毫米 英寸	毫米 英寸	毫米 英寸	Cr	Cor	毫米	转/分	转/分	转/分	转/分			
6300	10	0.3937	35	1.3779	11	0.4331	8.20	3.50	6	7.144	23000	27000	0.053
6301	12	0.4724	37	1.4567	12	0.4724	9.70	4.20	6	7.938	20000	24000	0.060
6302	15	0.5906	42	1.6535	13	0.5118	11.40	5.45	7	7.938	17000	21000	0.082
6303	17	0.6693	47	1.8504	14	0.5512	13.50	6.55	7	8.731	16000	19000	0.120
6304	20	0.7874	52	2.0472	15	0.5906	15.90	7.90	7	9.525	14000	17000	0.140
6305	25	0.9843	62	2.4409	17	0.6693	21.20	10.90	7	11.500	12000	14000	0.230
6306	30	1.1811	72	2.8346	19	0.748	26.70	15.00	8	12.000	10000	12000	0.350
6307	35	1.3779	80	3.1496	21	0.8268	33.50	19.10	8	13.494	8800	10000	0.460
6308	40	1.5748	90	3.5433	23	0.9055	40.50	24.00	8	15.081	7800	9200	0.630
6309	45	1.7716	100	3.937	25	0.9843	53.00	32.00	8	17.462	7000	8200	0.830
6310	50	1.965	110	4.3307	27	1.063	62.00	38.50	8	19.05	6400	7500	1.050
6311	55	2.1653	120	4.7244	29	1.1417	71.50	45.00	8	20.638	5800	6800	1.350
6312	60	2.362	130	5.1181	31	1.2205	82.00	52.00	8	22.225	5400	6300	1.700
6313	65	2.559	140	5.7087	33	1.2992	92.50	60.00	8	24.000	4900	5800	2.100
6314	70	2.7559	150	5.9055	35	1.378	104.00	68.00	8	25.400	4600	5400	2.500
6315	75	2.9528	160	6.2992	37	1.4567	113.00	77.00	8	26.988	4300	5000	3.000
6316	80	3.1496	170	6.6929	39	1.5354	123.00	86.50	8	28.575	4000	4700	3.600
6317	85	3.3465	180	7.0866	41	1.6142	133.00	97.00	8	30.163	3800	4500	4.250
6318	90	3.5433	190	7.4803	43	1.6929	143.00	107.00	8	32.000	3600	4200	4.900
6319	95	3.7402	200	7.874	45	1.7717	153.00	119.00	8	34.000	3300	3900	5.650
6320	100	3.937	215	8.2677	47	1.8504	173.00	141.00	8	36.512	3200	3700	7.000

### 深沟球轴承->63001系列



轴承 型号	孔径		外径		宽度		额定载荷 (KN)		钢球参数		极限转速		参考重量 千克
	d	D	B	动负荷	静负荷	数量	尺寸	脂	油	参考重量 千克			
	毫米英寸	毫米英寸	毫米英寸	Cr	Cor	毫米	转/分	转/分					
63001	12	0.4724	28	1.1024	12	0.4331	5.10	2.39	8	4.763	26000	30000	0.029
63002	15	0.5906	32	1.2598	13	0.4724	5.60	2.84	9	4.763	22000	26000	0.039
63003	17	0.6693	35	1.378	14	0.5118	6.80	3.35	10	4.763	20000	24000	0.052
63004	20	0.7874	42	1.6535	16	0.6299	9.40	5.05	9	6.350	18000	21000	0.086
63005	25	0.9843	47	1.8504	16	0.6299	10.10	5.58	10	6.350	15000	18000	0.100
63006	30	1.1811	55	2.1645	19	0.7480	13.20	8.30	11	7.144	13000	15000	0.160
63007	35	1.378	62	2.4409	20	0.7874	16.00	10.30	11	7.938	12000	14000	0.210
63008	40	1.5748	68	2.6772	21	0.8268	16.80	11.50	12	7.938	10000	12000	0.260
63009	45	1.7716	75	2.9528	23	0.9055	20.80	14.60	12	8.731	5600	6600	0.340
63010	50	1.9685	80	3.496	23	0.9055	21.60	16.00	13	8.731	5000	6000	0.370

### 深沟球轴承->16000系列



轴承 型号	孔径		外径		宽度		额定载荷 (KN)		钢球参数		极限转速		参考重量 千克
	d	D	B	动负荷	静负荷	数量	尺寸	脂	油	参考重量 千克			
	毫米英寸	毫米英寸	毫米英寸	Cr	Cor	毫米	转/分	转/分					
16001	12	0.4724	28	1.1024	7	0.2775	5.10	2.40	8	4.763	26000	30000	0.019
16002	15	0.5906	32	1.2598	8	0.315	5.60	2.80	9	4.763	22000	26000	0.025
16003	17	0.6693	35	1.3780	8	0.315	6.80	3.35	10	4.763	20000	24000	0.032
16004	20	0.7874	42	1.6535	8	0.315	7.90	4.50	10	5.556	18000	21000	0.051
16005	25	0.9843	47	1.8504	8	0.315	8.35	5.10	11	5.556	15000	18000	0.059
16006	30	1.1811	55	2.1645	9	0.3543	11.20	7.40	12	6.350	13000	15000	0.091
16007	35	1.3779	62	2.4409	9	0.3543	11.70	8.20	13	6.350	12000	14000	0.107
16008	40	1.5748	68	2.6772	9	0.3543	12.60	9.65	15	6.350	10000	12000	0.125
16009	45	1.7716	75	2.9528	10	0.3937	12.90	10.50	16	6.35	9200	11000	0.171
16010	50	1.9650	80	3.1496	10	0.3937	13.20	11.30	16	7.144	8400	9800	0.180
16011	55	2.1653	90	3.5433	11	0.433	18.60	15.30	16	7.938	7700	9000	0.258
16012	60	2.3620	95	3.7400	11	0.433	20.00	17.50	18	7.144	7000	8300	0.283
16013	65	2.5590	100	3.9370	11	0.433	20.50	18.70	20	7.144	6500	7700	0.307
16014	70	2.7559	110	4.3307	13	0.5118	24.40	22.60	15	9.525	6100	7100	0.441
16015	75	2.9528	115	4.5276	13	0.5118	25.00	24.00	16	9.525	5700	6700	0.464
16016	80	3.1496	125	4.9213	14	0.5512	25.40	25.10	15	11.112	5300	6200	0.597
16017	85	3.3465	130	5.1181	14	0.5512	25.90	26.20	16	11.112	5000	5900	0.626
16018	90	3.5433	140	5.5118	16	0.6299	33.50	33.50	15	12.700	4700	5600	0.848
16019	95	3.7402	145	5.7087	16	0.6299	34.50	35.00	16	12.700	4500	5300	0.885
16020	100	3.9370	150	5.9055	16	0.6299	35.00	36.50	17	12.700	4200	5000	0.910